



Safety data sheet

According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** DIESEL TREATMENT
- **Article number:** 386
- **Application of the substance / the preparation** Cleans, lubricates and kills micro organisms.
- **Details of the supplier of the safety data sheet**
- **Further information obtainable from:**
 WYNN OIL SOUTH AFRICA (PTY) LTD
 22 Mopedi Road,
 Sebenza, Edenvale
 1609
 Gauteng
 South Africa
 Tel: 2711 609 3708
 Fax: 2711 609 3708
 technical@wynns.co.za
- **Emergency telephone number:** Tel: 2711 609 3708

2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** -

· Dangerous components:

111-84-2	Nonane Xn R65; N R51/53 R10 ----- H226; H304; H411; H401	50-70%
	Diesel Fuel Additive Xn R20/21/22; N R51/53 R44 ----- H301; H311; H411; H332; H401	10-20%
	Fuel Biocide T R23/24/25; C R34; Xi R43; N R50/53 ----- H301; H311; H331; H314; H400; H410; H317	1-5%
1306-38-3	cerium dioxide T R23 ----- H330	1-5%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



C; Corrosive

R34: Causes burns.



Xn; Harmful

R20/21/22-65: Harmful by inhalation, in contact with skin and if swallowed. Harmful: may cause lung damage if swallowed.

(Contd. on page 2)



Trade name: **DIESEL TREATMENT**

(Contd. of page 1)



Xi; Sensitising

R43: *May cause sensitisation by skin contact.*



N; Dangerous for the environment

R51/53: *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

R10: *Flammable.*

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

N/A

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

C Corrosive

N Dangerous for the environment

· **Hazard-determining components of labelling:**

Nonane

Fuel Biocide

· **Risk phrases:**

10 Flammable.

20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

34 Causes burns.

43 May cause sensitisation by skin contact.

51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

2 Keep out of the reach of children.

26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

4 First aid measures

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

· **After eye contact:** *Rinse opened eye for several minutes under running water. Then consult a doctor.*

(Contd. on page 3)



Safety data sheet

According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

Trade name: DIESEL TREATMENT

(Contd. of page 2)

- **After swallowing:**
Call for a doctor immediately.
Drink plenty of water and provide fresh air. Call for a doctor immediately.

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Use neutralizing agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 4)



Trade name: DIESEL TREATMENT

(Contd. of page 3)

- **Ingredients with limit values that require monitoring at the workplace:**
The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- **Additional information:** *The lists valid during the making were used as basis.*
- **Personal protective equipment:**
- **General protective and hygienic measures:**
*Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.*
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

*The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.*

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- | | |
|---|------------------------------|
| · General Information | |
| · Appearance: | |
| · Form: | Liquid |
| · Colour: | As per product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| · Melting point/Melting range: | Undetermined. |
| · Boiling point/Boiling range: | 151 °C |
| · Flash point: | 31 °C |
| · Flammability (solid, gaseous): | Not applicable. |

(Contd. on page 5)



Safety data sheet
According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

Trade name: DIESEL TREATMENT

(Contd. of page 4)

· Ignition temperature:	205 °C
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	5.6 Vol %
· Vapour pressure at 20 °C:	4.7 hPa
· Density at 20 °C:	0.888 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	68.9 %
VOC (EC)	68.87 %
Solids content:	0.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Caustic effect on skin and mucous membranes.
- **on the eye:** Strong caustic effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:
Harmful
Corrosive
Irritant

(Contd. on page 6)

ZA



Safety data sheet

According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

Trade name: DIESEL TREATMENT

(Contd. of page 5)

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralized.
 Danger to drinking water if even small quantities leak into the ground.
 Also poisonous for fish and plankton in water bodies.
 Toxic for aquatic organisms

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	N/A
· ADR, IMDG, IATA	UN2922
· UN proper shipping name	2922 CORROSIVE LIQUID, TOXIC, N.O.S. (mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-m, NONANES), ENVIRONMENTALLY HAZARDOUS
· ADR	
· IMDG	CORROSIVE LIQUID, TOXIC, N.O.S. (mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-m, NONANES), MARINE POLLUTANT
· IATA	CORROSIVE LIQUID, TOXIC, N.O.S. (mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2-Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-m, NONANES)

(Contd. on page 7)

-ZA



Safety data sheet

According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

Trade name: DIESEL TREATMENT

(Contd. of page 6)

· **Transport hazard class(es)** N/A

· **ADR, IMDG**



· **Class** 8 Corrosive substances.
 · **Label** 8+6.1+3

· **IATA**



· **Class** 8 Corrosive substances.
 · **Label** 8+6.1+3

· **Packing group** N/A

· **ADR, IMDG, IATA** II

· **Environmental hazards:** Product contains environmentally hazardous substances: mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2Hisothiazol-3-one [EC no. 220-239-6] (3:1) mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-4-isothiazolin-3-one [EC no. 220-239-6] (3:1), Nonane

· **Marine pollutant:** Yes
 Symbol (fish and tree)

· **Special marking (ADR):** Symbol (fish and tree)

· **Special precautions for user** Warning: Corrosive substances.

· **Danger code (Kemler):** 86

· **EMS Number:** F-A,S-B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **ADR**

· **Limited quantities (LQ)** 1L

· **Transport category** 2

· **Tunnel restriction code** E

15 Regulatory information

· **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

C Corrosive

N Dangerous for the environment

(Contd. on page 8)

ZA



Trade name: DIESEL TREATMENT

(Contd. of page 7)

· **Hazard-determining components of labelling:**

Nonane
Fuel Biocide

· **Risk phrases:**

10 Flammable.
20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
34 Causes burns.
43 May cause sensitisation by skin contact.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
65 Harmful: may cause lung damage if swallowed.

· **Safety phrases:**

2 Keep out of the reach of children.
26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
36/37/39 Wear suitable protective clothing, gloves and eye/face protection.
45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **National regulations:**

Class	Share in %
I	2.3
NK	68.9

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H330 Fatal if inhaled.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H400 Very toxic to aquatic life.
H401 Toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H411 Toxic to aquatic life with long lasting effects.
R10 Flammable.
R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.
R23 Toxic by inhalation.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R34 Causes burns.
R43 May cause sensitisation by skin contact.
R44 Risk of explosion if heated under confinement.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R65 Harmful: may cause lung damage if swallowed.

(Contd. on page 9)



Safety data sheet
According to 91/155 EEC

Printing date 21.04.2015

Revision: 21.04.2015

Trade name: DIESEL TREATMENT

(Contd. of page 8)

· Department issuing MSDS:

WYNN OIL SOUTH AFRICA 9 PTY) LTD

22 Mopedi Road

Sebenza, Edenvale

1609

Gauteng

South Africa

Tel: 2711 609 3708

Fax: 2711 609 2218

technical@wynns.co.za

· Contact: 2711 609 3708**· * Data compared to the previous version altered.**

ZA