



Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** SILICONE LUBRICANT 200 ml
- **Article number:** 420
- **Application of the substance / the preparation**
Silicone based spray elastomer lubrication such as door hinges, sticky locks, draws, curtain rails and effective on rubber, plastic and nylon sliders
- **Details of the supplier of the safety data sheet**
- **Further information obtainable from:**
WYNN OIL SOUTH AFRICA (PTY) LTD
22 Mopedi Road,
Sebenza, Edenvale
1609
Gauteng
South Africa
Tel: 2711 609 3708
Fax: 2711 609 2218
technical@wynns.co.za
- **Emergency telephone number:** Tel: 2711 609 3708

2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

111-84-2	Nonane Xn R65; N R51/53 R10 H226; H304; H411; H401	50-70%
71-43-2	benzene T Carc. Cat. 1, Muta. Cat. 2 R45-46-48/23/24/25; Xn R65; Xi R36/38; F R11	20-40%
74-98-6	propane F+ R12	10-30%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xi; Irritant

R36/38: Irritating to eyes and skin.

F+; Extremely flammable

R12: Extremely flammable.

R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

(Contd. on page 2)

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: SILICONE LUBRICANT 200 ml

(Contd. of page 1)

· **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

· **Label elements**

· **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

F+ Extremely flammable

· **Hazard-determining components of labelling:**

benzene

· **Risk phrases:**

12 Extremely flammable.

36/38 Irritating to eyes and skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

29 Do not empty into drains.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· **Special labelling of certain preparations:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

4 First aid measures

· **After inhalation:** *In case of unconsciousness place patient stably in side position for transportation.*

· **After skin contact:** *Immediately wash with water and soap and rinse thoroughly.*

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** *If symptoms persist consult doctor.*

5 Firefighting measures

· **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **For safety reasons unsuitable extinguishing agents:** *Water with full jet*

· **Special hazards arising from the substance or mixture** *No further relevant information available.*

· **Protective equipment:** *No special measures required.*

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

(Contd. on page 3)

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: **SILICONE LUBRICANT 200 ml**

(Contd. of page 2)

- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:** Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

71-43-2 benzene

OEL (South Africa) Long-term value: 3 mg/m³, 1 ppm

74-98-6 propane

OEL (South Africa) Long-term value: 1800 mg/m³, 1000 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:** Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 4)

ZA

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: **SILICONE LUBRICANT 200 ml**

(Contd. of page 3)

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Aerosol
Colour: As per product specification

· **Odour:** Characteristic
 · **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44 °C

· **Flash point:** -97 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 205 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Not determined.

· **Explosion limits:**

Lower: 0.7 Vol %
Upper: 10.9 Vol %

· **Vapour pressure at 20 °C:** 8300 hPa

· **Density at 20 °C:** 0.95374 g/cm³

· **Relative density** Not determined.

(Contd. on page 5)

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: **SILICONE LUBRICANT 200 ml**

(Contd. of page 4)

· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	100.00 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

71-43-2 benzene

Oral	LD50	4894 mg/kg (rat)
Dermal	LD50	48 mg/kg (mouse)
Inhalative	LC50/4 h	9980 mg/l (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
- Water hazard class 3 (German Regulation) (Self-assessment): extremely hazardous for water

(Contd. on page 6)

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: **SILICONE LUBRICANT 200 ml**






(Contd. of page 5)

Do not allow product to reach ground water, water course or sewage system, even in small quantities.
 Danger to drinking water if even extremely small quantities leak into the ground.
 Harmful to aquatic organisms

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · ADR, IMDG, IATA | UN1950 |
| <ul style="list-style-type: none"> · UN proper shipping name · ADR · IMDG · IATA | 1950 AEROSOLS, ENVIRONMENTALLY HAZARDOUS AEROSOLS (NONANES), MARINE POLLUTANT AEROSOLS, flammable |
| <ul style="list-style-type: none"> · Transport hazard class(es) · ADR | <div style="display: flex; align-items: center; gap: 10px;">   </div> |
| <ul style="list-style-type: none"> · Class · Label | 2 5F Gases.
2.1 |
| <ul style="list-style-type: none"> · IMDG | |
| <div style="display: flex; align-items: center; gap: 10px;">   </div> | |
| <ul style="list-style-type: none"> · Class · Label | 2.1
2.1 |
| <ul style="list-style-type: none"> · IATA | |
| <div style="display: flex; align-items: center; gap: 10px;">  </div> | |
| <ul style="list-style-type: none"> · Class · Label | 2.1
2.1 |
| <ul style="list-style-type: none"> · Packing group · ADR, IMDG, IATA | -
Void |
| <ul style="list-style-type: none"> · Environmental hazards: | Product contains environmentally hazardous substances: Nonane |

(Contd. on page 7)

ZA

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: **SILICONE LUBRICANT 200 ml**

(Contd. of page 6)

- | | |
|---------------------------------|-------------------------------|
| · Marine pollutant: | Yes
Symbol (fish and tree) |
| · Special marking (ADR): | Symbol (fish and tree) |

- | | |
|---------------------------------------|-----------------|
| · Special precautions for user | Warning: Gases. |
| · Danger code (Kemler): | - |
| · EMS Number: | F-D,S-U |

- | | |
|--|-----------------|
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
|--|-----------------|

· Transport/Additional information:

- | | |
|----------------------------------|----|
| · ADR | |
| · Limited quantities (LQ) | 1L |
| · Transport category | 2 |
| · Tunnel restriction code | D |

15 Regulatory information

· Labelling according to EU guidelines:

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· Code letter and hazard designation of product:

Xi Irritant

F+ Extremely flammable

· Hazard-determining components of labelling:

benzene

· Risk phrases:

12 Extremely flammable.

36/38 Irritating to eyes and skin.

52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Safety phrases:

2 Keep out of the reach of children.

9 Keep container in a well-ventilated place.

29 Do not empty into drains.

45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material.

· Classification in accordance with Directive 75/324/EEC: Extremely flammable**· National regulations:**

Class	Share in %
III	25.0
NK	75.0

ZA

(Contd. on page 8)

Safety data sheet

According to 91/155 EEC

Printing date 01.09.2015

Revision: 01.09.2015

Trade name: SILICONE LUBRICANT 200 ml

(Contd. of page 7)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 *Flammable liquid and vapour.*

H304 *May be fatal if swallowed and enters airways.*

H401 *Toxic to aquatic life.*

H411 *Toxic to aquatic life with long lasting effects.*

R10 *Flammable.*

R11 *Highly flammable.*

R12 *Extremely flammable.*

R36/38 *Irritating to eyes and skin.*

R45 *May cause cancer.*

R46 *May cause heritable genetic damage.*

R48/23/24/25 *Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.*

R51/53 *Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.*

R65 *Harmful: may cause lung damage if swallowed.*

· **Department issuing MSDS:**

WYNN OIL SOUTH AFRICA (PTY) LTD

22 Mopedi Road

Sebenza, Edenvale

1609

Gauteng

South Africa

Tel: 2711 609 3708

Fax :2711 609 2218

technical@wynns.co.za

· **Contact:** 2711 609 3708

· *** Data compared to the previous version altered.**