



Safety data sheet

According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** WYNN'S ENGINE STOP LEAK.
- **Article number:** 502
- **Application of the substance / the preparation**
For minor oil leaks due to shrunken seals and shrunken valve stem oil seals. It will swell neoprene or rubber seals provided they are not damaged. It does not work on cork gaskets or other seals not made from rubber.
- **Details of the supplier of the safety data sheet**
- **Further information obtainable from:**
Wynn's South Africa
702 Main Pretoria Road
Wynberg
Sandton
2090
SOUTH AFRICA
Tel: 2711 786 9070
Fax: 2711 786 9069
- **Emergency telephone number:** Tel: 2711 786 9070

2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Blend of inorganic oxide, silicate, cellulose and carbonate.
- **Dangerous components:**
Not applicable

110-86-1	pyridine	Xn R20/21/22; F R11 H225; H302; H312; H332	1-5%
68649-42-3	Zinc Dialkyl Dithiophosphate	R53 H413	1-5%
8042-47-5	Mineral Oil		50-70%
80584-90-3	sn - 100 (Agip) sn 90		30-40%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xi; Irritant

R36/38: Irritating to eyes and skin.

R53: May cause long-term adverse effects in the aquatic environment.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Safety data sheet
According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 1)

- **Label elements**

- **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**

Xi Irritant

- **Risk phrases:**

36/38 Irritating to eyes and skin.

53 May cause long-term adverse effects in the aquatic environment.

- **Safety phrases:**

2 Keep out of the reach of children.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

5 Firefighting measures

- **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

ZA

(Contd. on page 3)



Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 2)

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about fire - and explosion protection:** No special measures required.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

110-86-1 pyridine

OEL (South Africa)	Short-term value: 30 mg/m ³ , 10 ppm Long-term value: 15 mg/m ³ , 5 ppm
IOELV (EU)	15 mg/m ³ , 5 ppm

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)



Safety data sheet
According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 3)

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties

· General Information

· Appearance:

Form: Liquid
Colour: As per product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

· **Flash point:** Not applicable.

· **Flammability (solid, gaseous):** Not applicable.

· Ignition temperature:

Decomposition temperature: Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined.

Upper: Not determined.

· **Vapour pressure:** Not determined.

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

· **Evaporation rate** Not determined.

· Solubility in / Miscibility with

water: Not miscible or difficult to mix.

· **Segregation coefficient (n-octanol/water):** Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

· Solvent content:

Organic solvents: 0.0 %

VOC (EC) 0.00 %

· **Other information** No further relevant information available.

ZA

(Contd. on page 5)



Safety data sheet

According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 4)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

110-86-1 pyridine

Oral	LD50	891 mg/kg (rat)
Dermal	LD50	1121 mg/kg (rabbit)

· **Primary irritant effect:**

· **on the skin:**

Irritant to skin and mucous membranes.

Slightly Irritant

· **on the eye:** Irritating effect.

· **Sensitization:** Slightly Irritant

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number** N/A

(Contd. on page 6)

ZA



Safety data sheet
According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 5)

· UN proper shipping name	
· ADR	Void
· Transport hazard class(es)	N/A
· Packing group	N/A
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

· **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xi Irritant

· **Risk phrases:**

36/38 Irritating to eyes and skin.

53 May cause long-term adverse effects in the aquatic environment.

· **Safety phrases:**

2 Keep out of the reach of children.

23 Do not breathe gas/fumes/vapour/spray (appropriate wording to be specified by the manufacturer).

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

· **National regulations:**

Class	Share in %
NK	3,1

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H413 May cause long lasting harmful effects to aquatic life.

R11 Highly flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R53 May cause long-term adverse effects in the aquatic environment.

(Contd. on page 7)



Safety data sheet
According to 91/155 EEC

Printing date 24.11.2011

Revision: 23.11.2011

Trade name: WYNN'S ENGINE STOP LEAK.

(Contd. of page 6)

· Department issuing MSDS:

Wynn`s South Africa
72 Main Pretoria Road
Wynberg
Sandton
2090

SOUTH AFRICA
Tel: 2711 786 9070
Fax: 2711 786 9069

· * Data compared to the previous version altered.

ZA