



Safety data sheet

According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** WYNNS ENGINE START
- **Article number:** 525
- **Application of the substance / the preparation**
Use to start Diesel trucks, tractors and stubborn lawn mowers. Contains friction proofing to avoid dry start up.
- **Details of the supplier of the safety data sheet**
- **Further information obtainable from:**
WYNN OIL SOUTH AFRICA (PTY) LTD
22 Mopedi Road,
Sebenza, Edenvale
1609
Gauteng
South Africa
Tel: 2711 609 3708
Fax: 2711 609 2218
technical@wynns.co.za
- **Emergency telephone number:** Tel: 2711 609 3708

2 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | | |
|---------|---------------|---|--------|
| 60-29-7 | diethyl ether | Xn R22; F+ R12 R19-66-67 H224; H302; H336 | 50-60% |
| 74-98-6 | propane | F+ R12 | 10-15% |

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

3 Hazards identification

- **Classification of the substance or mixture**
- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

Xn; Harmful

R22: Harmful if swallowed.

F+; Extremely flammable

R12: Extremely flammable.

R19-67: May form explosive peroxides. Vapours may cause drowsiness and dizziness.

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

(Contd. on page 2)



Safety data sheet According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

Trade name: WYNNS ENGINE START

(Contd. of page 1)

- **Label elements**

- **Labelling according to EU guidelines:**

Observe the general safety regulations when handling chemicals.

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**

Xn Harmful

F+ Extremely flammable

- **Hazard-determining components of labelling:**

diethyl ether

- **Risk phrases:**

12 Extremely flammable.

19 May form explosive peroxides.

22 Harmful if swallowed.

67 Vapours may cause drowsiness and dizziness.

- **Safety phrases:**

1/2 Keep locked up and out of the reach of children.

3 Keep in a cool place.

29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

46 If swallowed, seek medical advice immediately and show this container or label.

- **Classification in accordance with Directive 75/324/EEC: Extremely flammable**

4 First aid measures

- **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately rinse with water.

- **After eye contact:** Rinse opened eye for several minutes under running water.

- **After swallowing:** Call for a doctor immediately.

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.

- **For safety reasons unsuitable extinguishing agents:** Water with full jet

- **Special hazards arising from the substance or mixture** No further relevant information available.

- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

- **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 3)



Trade name: WYNNS ENGINE START

(Contd. of page 2)

- **Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep container tightly sealed.
Do not seal receptacle gas tight.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

60-29-7 diethyl ether

| | |
|--------------------|---|
| OEL (South Africa) | Short-term value: 1500 mg/m ³ , 500 ppm Long-term value: 1200 mg/m ³ , 400 ppm |
| IOELV (EU) | Short-term value: 616 mg/m ³ , 200 ppm Long-term value: 308 mg/m ³ , 100 ppm |

74-98-6 propane

| | |
|--------------------|--|
| OEL (South Africa) | Long-term value: 1800 mg/m ³ , 1000 ppm |
|--------------------|--|

- **Additional information:** The lists valid during the making were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.

(Contd. on page 4)



Safety data sheet

According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

Trade name: WYNNS ENGINE START

(Contd. of page 3)

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

| | |
|------------------|------------------------------|
| Form: | Aerosol |
| Colour: | As per product specification |
| Odour: | Characteristic |
| Odour threshold: | Not determined. |

· **pH-value:** Not determined.

· **Change in condition**

| | |
|------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
| Boiling point/Boiling range: | -44 °C |

· **Flash point:** -97 °C

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 170 °C

· **Decomposition temperature:** Not determined.

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** May form explosive peroxides.

· **Explosion limits:**

| | |
|--------|------------|
| Lower: | 1.7 Vol % |
| Upper: | 36.0 Vol % |

· **Vapour pressure at 20 °C:** 8300 hPa

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapour density** Not determined.

(Contd. on page 5)



Safety data sheet

According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

Trade name: WYNNS ENGINE START

(Contd. of page 4)

- | | |
|---|--|
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Organic solvents: | 75.0 % |
| VOC (EC) | 75.00 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**

- **LD/LC50 values relevant for classification:**

60-29-7 diethyl ether

| | | |
|------------|----------|------------------|
| Oral | LD50 | 1215 mg/kg (rat) |
| Inhalative | LC50/4 h | 73000 mg/l (rat) |

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Additional ecological information:**

- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 6)



Safety data sheet
According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

Trade name: WYNNS ENGINE START

(Contd. of page 5)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

| | |
|--|-----------------|
| · UN-Number | |
| · ADR, IMDG, IATA | UN1950 |
| · UN proper shipping name | |
| · ADR | 1950 AEROSOLS |
| · IMDG, IATA | AEROSOLS |
| · Transport hazard class(es) | 2 5F Gases |
| · Packing group | - |
| · Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Not applicable. |
| · EMS Number: | F-D,S-U |
| · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |

15 Regulatory information

- **Labelling according to EU guidelines:**
Observe the general safety regulations when handling chemicals.
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.
- **Code letter and hazard designation of product:**
Xn Harmful
F+ Extremely flammable
- **Hazard-determining components of labelling:**
diethyl ether
- **Risk phrases:**
12 Extremely flammable.
19 May form explosive peroxides.
22 Harmful if swallowed.
67 Vapours may cause drowsiness and dizziness.
- **Safety phrases:**
1/2 Keep locked up and out of the reach of children.
3 Keep in a cool place.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

(Contd. on page 7)



Safety data sheet
According to 91/155 EEC

Printing date 23.06.2015

Revision: 05.12.2014

Trade name: WYNNS ENGINE START

(Contd. of page 6)

46 If swallowed, seek medical advice immediately and show this container or label.

· **Classification in accordance with Directive 75/324/EEC:** Extremely flammable

· **National regulations:**

| Class | Share in % |
|-------|------------|
| NK | 75.0 |

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H224 Extremely flammable liquid and vapour.

H302 Harmful if swallowed.

H336 May cause drowsiness or dizziness.

R12 Extremely flammable.

R19 May form explosive peroxides.

R22 Harmful if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:**

WYNN OIL SOUTH AFRICA (PTY) LTD

22 Mopedi Road

Sebenza, Edenvale

1609

Gauteng

South Africa

Tel: 2711 609 3708

Fax :2711 609 2218

technical@wynns.co.za

· **Contact:** 2711 609 3708

· *** Data compared to the previous version altered.**